

P/N: SDI-SPLIT41

Item Name: TopX SDI 1x4 SPLITTER WITH AMPLIFIER

Function: This 1x4 SDI splitter distributes one SDI signal to 4 SDI outputs simultaneously. It supports full range of SDI signal formats including 3G-SDI, HD-SDI, SD-SDI with easy operation and high reliability. Using broadcast quality processing technology, it delivers high definition, lossless and lag-free distribution. This splitter can be widely used in SDI broadcast room, no-linear editing field, CCTV security system and training showroom etc.

Specification:

- Material: Metal case
- Input: 1 x SDI BNC (HD-SDI/SD-SDI/3G-SDI)
- Output: 4 x SDI BNC (HD-SDI/SD-SDI/3G-SDI)
- SDI standard compatibility: SMPTE 424M, SMPTE 292M and SMPTE 259M-C
- SDI speed rate: 270~2970MB/s
- SDI input/output resolution: up to 1080p@60hz
- With LED indicators to show working status
- Supports input/output distance up to 400m for SD-SDI signal, 200m for HD-SDI signal, 100m for 3G-SDI signal theoretically (real distance subject to cable quality)
- Power adapter: 12V1A 5.5/2.1 (included)

Only support SDI signal, Only support 1080P NOT 4K, Only support BNC-BNC 75Ω coaxial cable, can't function reversely

Photo reference:

